





MINITRON MEGATRON GIGATRON

The first high* load positive feeder

Advanced High Tech Solutions for Coil and Motor Winding **Process Control**



TOP QUALITY & PRODUCTIVITY

HIGH FLEXIBILITY USER-FRIENDLY

MOTOR & COIL WINDING TECHNOLOGY LINE

The Ultimate Innovation in Wire Constant Tension Feeding.

MINITRON - MEGATRON - GIGATRON are one of the latest results from BTSR INTERNATIONAL, a worldwide leading company in the design of high tech solutions and innovation development in a wide variety of industrial sectors.

MINITRON - MEGATRON - GIGATRON represents a revolutionary new generation Wire Constant Tension Feeding devices, unique in terms of functionality and performances, capable of adjusting with utmost accuracy the tension of the wire in motor and coil winding processes.

An innovative Solution based on the BTSR PATENTS Dual-Drive Feeding System, Tension Profiler Function and Double Loop Control System bringing new and unique measurable benefits in terms of TOP Quality Control and Production Efficiency in coil winding processes.



MINITRON - MEGATRON - GIGATRON

- TOP Quality Standards Goal are ensured by the high-est coil winding quality and repeatability, thanks to BTSR 'Double Closed Loop' Technology guaranteeing the most accurate and precise wire tension control.
- TOP Versatility is guaranteed by Fully programmable parameters according to the wire requirements and possibility to dynamically modify the wire control tension according to the operating stage ('Tension Profiler' Function).
- TOP Process Production Efficiency is enhanced by dra-matic reduction of wire breakages.
- TOP Productivity is guaranteed by the capability to work at the maximum possible process speed.
- Minimized Labour Costs is possible thanks to the us-er-friendly programming options and no consumable parts - Easy maintenance.
- Wide application ranges are possible thanks to the wide wire tension and diameter range of MINITRON - MEGATRON - GIGATRON.
- Centralized programming and monitoring is possible thanks to MATRIX TOUCH COIL controller which will allow you to program and control MINITRON - MEGATRON -GIGATRON units and monitoring the whole process production status also in graphical form.





FEATURES

Tension profiler function (BTSR patent)

Possibility to program up to 3 different wire feeding tension values without any interface/ connection to the winding machine or up to 4 different wire feeding tension values during winding cycle, utilizing two digital winding machine output.

Double closed control loop system (BTSR patent)

Featuring simultaneous dual control on both wire feeding tension and Length of Wire Absorption (LWA) for a complete tension feeding control along the whole wire path (from the feeding bobbins to the final coil).

Programmable wire 'storage and release capability (BTSR patent)

Able to manage sudden wire absorption or release during the working process and simultaneously keeping the wire feeding tension at the set value.

Full input digital motor torque control (BTSR patent)

Detect and adjust input feeding tension anomaly, warning and stopping process before wire could be damaged thus avoiding any bad quality production.

• Pc link web coil software

For Industry 4.0 - Collect uniform data to monitor the entire production, ensuring an homogenous data collection also in case of new and old winding machines fleet.



BENEFITS

• Production process efficiency maximization

Able to maximize the working ramps, machine speed, thus dramatically reducing at the same time wire breakages, scraps, therefore granting fast Return On Investment (ROI).

A wide application range

MINITRON MEGATRON GIGATRON are single device capable to cover a very wide wire tension and diameter range.

Labour costs minimized

Thanks to the user-friendly programming options and easy and quick machine setup.

Maintenance costs minimized

No consumable mechanical parts due to the feeding technology which guarantee absence of parts frictioning / breaking allowing a very easy maintenance.

Advanced graphic display

Real-time working parameters monitoring, such as: Wire Speed (LWA) – Real time Wire Tension – TI motor Torque Index – QI tension Quality Index and Working phase.

• A compact solution

Easy plug & play installation.





MINITRON MEGATRON & GIGATRON




THE FIRST HIGH-LOAD - POSITIVE FEEDER

DESCRIPTION	MINITRON	MEGATRON	GIGATRON
Display tension range	0 – 5.000 g (cN)	0 – 10.000 g (cN)	0 – 20.000 g (cN)
Programmable Tension range	50g ÷ 4.000g (cN)	100g ÷ 9.000g (cN)	200g ÷ 18.000g (cN)
Programmable Tension resolution	10 grams		
Wire diameter range	0,08 Up to 1.038 mm	0,08 Up to 1,5 mm	0,12 Up to 2,25 mm
	40 up to 18AWG	40 up to 14.5AWG	36,5 up to 11.2AWG
Feeding speed range	÷ 12,5 m/s // ÷ 750 mt/min		
LWA resolution (meter)	± 1 mm		
AUTO- LWA and alarm range setting	Tension LWA ± 1 % upto ± 25 %		
	Meter LWA ± 0,1 mt up to 20 mt.		
OEM machine computer	Standard: RS485, Canbus		
interface Through SMDIN WEB COIL	Optional: Profinet, Ethernet IP, Ethercat Other on demand		
Power supply voltage	48VDC ± 10%		
Overall Dimensions (mm)	L x 126 W x 170 h		
Minimum Air Pressure	4 bar		
Weight	10,2 Kg	11,8 Kg	14,3 Kg



TOTAL QUALITY CONTROL - FROM WIRE COIL TO FINAL COILED PRODUCT FIRST CLOSED LOOP - MOTOR TORQUE **SECOND CLOSED LOOP - LWA**





DOUBLE CLOSED CONTROL LOOP (BTSR Patent)

MOTOR TORQUE (BTSR Patent)


1st closed loop

Total Input Controls

Operated by the motor control force (Torque). Detects and adiust

any input wire tension variation caused by:

- Input tension variation (full/empty feeding bobbin)
- Input wire entanglement



LWA Length of Wire Absorbed (BTSR Patent)

2nd closed loop

Total Output Controls

Operated by means of multiple motor controls, Speed/Wire consumption.

Detects and monitor:

- Any dimensional variation of coil formers.
- A wrong wire dimension (diameter/AWG).
- Accumulation of dirtiness inside the wire quide
- Damage of the wire guide.
- Any mechanical variation or friction on the contact points after the tension feeder device (Minitron - Megatron - Gigatron).
- Wire passing through the wire guides with different angles and frictions (wrong thread-up).

CONSTANT TENSION VALUE GUARANTEED

Output Wire Tension (LIGHT BLUE color) is kept constant at the set value, despite of input wire feeding tension variations (RED color) and/or wire speed variations (GREEN color) during the working process.



KEEP UNDER CONTROL THE WHOLE PROCESS WITH BTSR TECHNOLOGY PC LINK STUDIO & PC LINK WEB COIL (BTSR PATENT)

PC LINK STUDIO - Suitable to update Minitron Megatron & Gigatron software. Allow deep quality analysis of the coil process and machine development.

PC LINK WEB COIL - Suitable to monitor the whole department. Minitron Megatron & Gigatron can be installed on any type and model of new or old coil winding machines. Minitron Megatron & Gigatron + PC LINK SOFTWARE allow monitoring and programming the whole coil winding machines park (which can be not necessarily homogenous).

It is an unique INDUSTRY 4.0 remote programming monitoring & evaluation tool. This smart WIRE Feeding Control has been created to ease the programming of Minitron Megatron & Gigatron by means of a very intuitive interface, thus allowing on site monitoring, quality check, production monitoring and forecast analysis.

PC LINK WEB COIL is fully compatible with IOS and Android devices as it is based on web technology.





MATRIX TOUCH COIL TERMINAL

Centralized programming and monitoring is possible thanks to MATRIX TOUCH COIL controller which will allow you to program and control MINITRON - MEGATRON - GIGATRON units and monitoring the whole process production status also in graphical form.





