

TENSIONERS - FINE WIRE, LOW COST

SPECIFICATION

These mechanical tensioners provide precision control of winding tension for wires in the range from 0.02 mm to 2.0 mm.

The arm position provides feedback to the system, adjusting the main friction wheel to regulate and maintain constant tension during the winding cycle.

Felt pads provide pre-tension and remove dust and other debris from the wire.

Ceramic eyelets and roller guides at each point of contact protect insulation from mechanical damage, and the guide wire.

The performance of these units is exceptional given the low cost, providing outstanding value for money.

*The wire sizes shown are a guide only, for copper magnet wire at recommended "Standard Tension". The tension required in practical applications may vary considerably.



Models TC3S -TCM	Model TCL-X/TCLL-X	Model TC3L
---------------------	-----------------------	---------------

Model Type	Min Tension (grams)	Max Tension (grams)	Min Wire Gauge (mm)*	Max Wire Gauge (mm)*
TC3S	2	11	0.02	0.04
TCSS-X	7	30	0.03	0.06
TCSS	9	50	0.04	0.08
TCS-E	20	130	0.06	0.13
TCS	40	200	0.08	0.16
TCM	90	500	0.16	0.25
TCL-X	200	2000	0.20	0.60
TCLL-X	1000	5000	0.50	1.2
TC3L	2000	10000	0.70	2.0

We aim to be much more than a machinery supplier. Our team has a vast range of winding experience and is able to offer help and advice on all aspects of coil winding, from tooling design to machine choice and set-up.

COIL WINDING SOLUTIONS YOU CAN RELY ON

WORKING WITH LOCAL PARTNERS IN THE FOLLOWING COUNTRIES; Austria, Czech Republic, Germany, Hungary, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden.

Unit 5L, Delta Drive, Tewkesbury, Glos. GL20 8HB. United Kingdom.

